

CADET



INVITING WARMTH





APEX72 Above all, more room

- Gain warmth and living space—mounts high on wall
- Two outlet grill options; hexagonal and louvered

cover: 12"W x 8-1/2"H x 1"D
rough-in: 10"W x 7-7/8"H x 4"D

Heater assemblies require orient ring, CC or CCSM wall can, decorative cover and electronic thermostat
Additional accessories on page 2



part	model	description	watts	volts	amps	btus	wt/lbs
65402	HWC101K	complete kit with orient ring, CC wall can, ACL decorative cover and TH114 electronic thermostat	1000	120	8.3	3415	10.1
65403	HWC102K		240	240	4.2		
65316	HW051	heater assembly only	500	120	4.2	1710	4.7
65314	HW101	"	1000	120	8.3	3415	4.7
65315	HW151	"	1500	120	12.5	5120	4.7
65313	HW038	"	375	208	1.8	1280	4.7
65312	HW058	"	525	208	2.5	1795	4.7
65311	HW078	"	750	208	3.6	2560	4.7
65310	HW108	"	1000	208	4.8	3415	4.7
65309	HW128	"	1200	208	5.8	4095	4.7
65308	HW168	"	1600	208	7.7	5460	4.7
65305	HW052	"	500	240	2.1	1710	4.7
65304	HW082	"	800	240	3.3	2730	4.7
65303	HW102	"	1000	240	4.2	3415	4.7
65302	HW132	"	1300	240	5.4	4440	4.7
65301	HW162	"	1600/1200	240/208	6.7/5.7	5460/4095	4.7
67129	ACL	decorative cover for model HW with louver outlet grill, single pack or 5-pack, white					1.3
67131	ACL5		5.3				
67130	ACH	decorative cover for model HW with hexagonal outlet grill, single pack or 5-pack, white					1.3
67132	ACH5		5.3				
67051	OR	orient ring for model HW, single pack or 10-pack					1.9
67050	OR10		11.2				

COM-PAK EnergyPlus More comfort, less energy

- Use up to 30% less energy with automatically adjusting wattage and variable speed fan
- Built-in digital thermostat

grill: 9"W x 12"H x 5/8"D
rough-in: 8"W x 10-1/8"H x 4"D

Heater assemblies require CC or CCSM wall can and grill kit
Additional accessories on page 2

Temperature setpoint range 40°F to 86°F



part	model	description	watts	volts	amps	btus	wt/lbs
65215	CEC163TW	complete unit with thermostat, wall can and grill	1000/1600/1500	120/240/208	8.3/6.7/7.2	3415/5460/5120	8.1
65203	CE083T	heater assembly multi-volt with thermostat	500/800/750	120/240/208	4.2/3.3/3.6	1710/2730/2560	4.4
65204	CE163T	"	1000/1600/1500	120/240/208	8.3/6.7/7.2	3415/5460/5120	4.4
65208	CE162T	heater assembly single-volt with thermostat	1600	240	6.7	5460	4.4
65252	CEGW	grill kit for model CE, white					1.4

NEW

REGISTER

Powerful performance for any room

- Enjoy complete warmth, thanks to a powerful fan
- Vent-style grill blends in with any décor

grill: 14"W x 7-3/8"H x 1"D
rough-in: 12-3/4"W x 6"H x 4"D

Heater assemblies require RMC wall can, grill kit and thermostat



part	model	description	watts	volts	amps	btus	wt/lbs
63315	RMC151W	complete unit with wall can and grill	500/1000/2500	120	4.2/8.3/12.5	1710/3415/5120	9.4
63316	RMC208W	"	2000	208	9.6	6825	9.4
63314	RMC162W	"	700/900/1600 525/675/1200	240/208	2.9/3.8/6.7 2.5/3.3/5.8	2390/3075/5460 1795/2305/4095	9.4
63313	RMC202W	"	2000/1500	240/208	8.3/7.2	6825/5120	9.4
00308	RM151	heater assembly only	500/1000/1500	120	4.2/8.3/12.5	1710/3415/5120	4.9
00310	RM108	"	1000	208	4.8	3415	4.9
00323	RM158	"	1500	208	7.2	5120	4.9
00313	RM168	"	700/900/1600	208	3.4/4.3/7.7	2390/3175/5460	4.9
00309	RM208	"	2000	208	9.6	6825	4.9
00311	RM102	"	1000/750	240/208	4.2/3.6	3415/2560	4.9
00307	RM162	"	700/900/1600 525/675/1200	240/208	2.9/3.8/6.7 2.5/3.3/5.8	2390/3075/5460 1795/2305/4095	4.9
00306	RM202	"	2000/1500	240/208	8.3/7.2	6825/5120	4.9
00322	RM222	"	2250/1687	240/208	9.4/8.1	7680/5760	4.9
00275	RMGW	grill kit for model RM, single pack, white or almond					1.7
00276	RMGA						
63113	RMGW5	grill kit for model RM, 5-pack, white or almond					7.4
63114	RMGA5						
63115	RMC	wall can for model RM, single pack or 5-pack					3.7
63116	RMC5		14.3				
63123	RMT2W	built-in thermostat kit for model RM, double pole, 40°F to 85°F, white or almond		120/208/240	25		.4
63124	RMT2A						

COM-PAK MAX

Versatile, multi-watt warmth

- Enjoy years of reliable use with our sturdiest sealed element
- Fits any application with horizontal or vertical options

grill: 12"W x 9"H x 1"D or 9"W x 12"H x 1"D
rough-in: 10-1/8"W x 8"H x 4"D or 8"W x 10-1/8"H x 4"D

Accessories below
Heater assemblies require CC or CCSM wall can, grill kit, and may require a thermostat



part	model	description	watts	volts	amps	btus	wt/lbs
65030	CM168	heater assembly only	700/900/1600	208	3.4/4.3/7.7	2390/3075/5460	5
65008 65009	CM208 CM208T	heater assembly only heater assembly with thermostat	500/800/1200/1500/2000	208	2.4/3.9/5.8/7.2/9.6	1710/2730/4095/5120/6825	5 5
65001 65002	CM162 CM162T	"	700/900/1600 525/675/1200	240/208	2.9/3.8/6.7 2.5/3.3/5.8	2390/3075/5460 1795/2305/4895	5 5
65003 65004	CM202 CM202T	"	500/800/1200/1500/2000 375/600/900/1125/1500	240/208	2.1/3.3/5.0/6.3/8.3 1.8/2.9/4.3/5.4/7.2	1710/2730/4095/5120/6825 1280/2050/3075/3840/5120	5 5

COM-PAK BATH

Warmth for every morning

- Built-in thermostat and 60-minute timer
- Special coating on heating elements prevents rust in moist bathroom environments
- Provides quick and efficient warmth

grill: 10"W x 12-5/8"H x 1/2"D
rough-in: 8"W x 10-1/8"H x 4"D

Additional accessories below
Heater assemblies require CC wall can and grill kit



part	model	description	watts	volts	amps	btus	wt/lbs
65101	CBC103TW	complete unit with wall can, grill, thermostat and timer, multi-volt	1000	120/240	8.3/4.2	3415	8
65105	CBC132TW	complete unit with wall can, grill, thermostat and timer, multi-watt	500/800/1300 375/600/975	240/208	2.1/3.3/5.4 1.8/2.9/4.5	1710/2730/4440 1280/2050/3300	8
65103	CB103T	heater assembly with thermostat and timer, multi-volt	1000	120/240	8.3/4.2	3415	5
65104	CB132T	heater assembly with thermostat and timer, multi-watt	500/800/1300 375/600/975	240/208	2.1/3.3/5.4 1.8/2.9/4.7	1710/2730/4440 1280/2050/3300	5
65110 65150	CBGW CBGW5	grill kit for model CB, single or 5-pack, white					1.6 7.1

WALL HEATER ACCESSORIES (MODELS CS, CM, CE, CB, CST, HW)

NEW

NEW

part	model	description	volts	amps	wt/lbs
67061 67060	CC CC10	wall can for models CS, CM, CE, CB, or HW, single or 10-pack			2.8 22.5
69111 69112 69110	CCSMW CCSMA CCSMB	surface mount wall can for models CS, CM, CE, or HW, 9-13/16"W X 12-3/4"H X 4-7/16"D, white, almond or black			4.4
67079 67081	CGW CGW10	grill kit vertical for models CS, CM, single or 10-pack, white			1.6 12.2
67075 67080	CGA CGA10	grill kit vertical for models CS, CM, single or 10-pack, almond			1.6 12.2
67082 67083	CGB CGB10	grill kit vertical for models CS, CM, single or 10-pack, black			1.6 12.2
65005 65006	CMGW CMGW5	grill kit horizontal for models CS, CM, single or 5-pack, white			2.5 8.2
65015 65016	CMGA CMGA5	grill kit horizontal for models CS, CM, single or 5-pack, almond			2.5 8.2
67063 67065	CTT1W CTT1A	built-in thermostat kit for models CS, CST, CM, single pole, 40°F to 85°F, white or almond	120/208/240	22	.3
67064 67066	CTT2W CTT2A	built-in thermostat kit for models CS, CST, CM, double pole, 40°F to 85°F, white or almond	120/208/240	22	.3
67067 67068	CTTP CTT2P	built-in thermostat kit, tamperproof for models CS, CST, CM, single or double pole, 40°F to 85°F	120/208/240	22	.3
67105 67100	CAMW CAMA	adapter plate for models CS, CM, CE, or CB, 18-1/2"W x 22"H, white or almond			3.4
67115 67110	SAMW SAMA	adapter plate for models CS, CM, CE, or CB, 12"W x 21-1/4"H, white or almond			1.9
67088	FWAP	conversion kit FW to CS repurposes outdated model FW wall can and grill, use with model CS heater assembly			1.6

COM-PAK

Perfectly simple warmth for any room

- Warm up in a hurry with a fast-heating coil element
- Ceiling installation with models 1,500 watts or less

grill: 9"W x 12"H x 1"D
rough-in: 8"W x 10-1/8"H x 4"D

Accessories on page 2

Heater assemblies require CC or CCSM wall can, grill kit, and may require a thermostat



part	model	description	watts	volts	amps	btus	wt/lbs
67508	CSC101TW	complete unit with wall can, thermostat and white grill	1000	120	8.3	3415	7.2
67509	CSC151TW	"	1500	120	12.5	5120	7.2
67505	CSC102TW	"	1000/750	240/208	4.2/3.6	3415/2560	7.2
67506	CSC152TW	"	1500/1125	240/208	6.3/5.4	5120/3840	7.2
67507	CSC202TW	"	2000/1500	240/208	8.3/7.2	6825/5120	7.2
67580	CSC101TA	complete unit with wall can, thermostat and almond grill	1000	120	8.3	3415	7.2
67581	CSC151TA	"	1500	120	12.5	5120	7.2
67577	CSC102TA	"	1000/750	240/208	4.2/3.6	3415/2560	7.2
67578	CSC152TA	"	1500/1125	240/208	6.3/5.4	5120/3840	7.2
67579	CSC202TA	"	2000/1500	240/208	8.3/7.2	6825/5120	7.2
67549	CSC101W	complete unit with wall can and white grill	1000	120	8.3	3415	7
67553	CSC151W	"	1500	120	12.5	5120	7
67541	CSC102W	"	1000/750	240/208	4.2/3.6	3415/2560	7
67543	CSC152W	"	1500/1125	240/208	6.3/5.4	5120/3840	7
67544	CSC202W	"	2000/1500	240/208	8.3/7.2	6825/5120	7
67550	CS051	heater assembly only					3.2
67560	CS051T	heater assembly with thermostat	500	120	4.2	1710	3.3
67515	CS101	"	1000	120	8.3	3415	3.2
67523	CS101T	"					3.3
67516	CS151	"	1500	120	12.5	5120	3.2
67524	CS151T	"					3.3
67563	CS058	"	563	208	2.7	1925	3.2
67573	CS058T	"					3.3
67564	CS078	"	750	208	3.6	2560	3.2
67589	CS078T	"					3.3
67557	CS108	"	1000	208	4.8	3415	3.2
67586	CS108T	"					3.3
67569	CS118	"	1125	208	5.4	3840	3.2
67598	CS118T	"					3.3
67571	CS158	"	1500	208	7.2	5120	3.2
67599	CS158T	"					3.3
67517	CS208	"	2000	208	9.6	6825	3.2
67525	CS208T	"					3.3
67584	CS052	"	500/375	240/208	2.1/1.8	1710/1280	3.2
67585	CS052T	"					3.3
67510	CS072	"	750/563	240/208	3.1/2.7	2560/1925	3.2
67518	CS072T	"					3.3
67511	CS102	"	1000/750	240/208	4.2/3.6	3415/2560	3.2
67519	CS102T	"					3.3
67512	CS122	"	1250/937	204/208	5.2/4.5	4260/3200	3.2
67520	CS122T	"					3.3
67513	CS152	"	1500/1125	240/208	6.3/5.4	5120/3840	3.2
67521	CS152T	"					3.3
67514	CS202	"	2000/1500	240/208	8.3/7.2	6825/5120	3.2
67522	CS202T	"					3.3

COM-PAK TWIN

Ideal warmth for larger areas

- Ideal for large rooms, open areas and entryways
- Warms up quickly with fast-heating coil elements and efficient fans

grill: 16-1/4"W x 12"H x 1"D
rough-in: 14-1/2"W x 10-1/8"H x 4"D

Additional accessories on page 2

Heater assemblies require CTC wall can, grill kit, and may require a thermostat



part	model	description	watts	volts	amps	btus	wt/lbs
67526	CSTC302TW	complete unit with wall can, thermostat and white grill	3000/2250	240/208	12.5/10.8	10240/7680	12.3
67527	CSTC402TW	"	4000/3000	240/208	16.7/14.4	13650/10240	12.3
67582	CSTC302TA	complete unit with wall can, thermostat and almond grill	3000/2250	240/208	12.5/10.8	10240/7680	12.3
67583	CSTC402TA	"	4000/3000	240/208	16.7/14.4	13650/10240	12.3
67574	CST308	heater assembly only					6.9
67534	CST308T	heater assembly with thermostat	3000	208	14.4	10240	7.1
67530	CST408	"	4000	208	19.2	13650	6.9
67533	CST408T	"					7.1
67528	CST302	"	3000/2250	240/208	12.5/10.8	10240/7680	6.9
67531	CST302T	"					7.1
67529	CST402	"	4000/3000	240/208	16.7/14.4	13650/10240	6.9
67532	CST402T	"					7.1
68005	CTC	wall can for model CST, single pack					4.4
67089	CTGW	grill kit for model CST, single pack, white or almond					3
67090	CTGA						
69104	CTS4W	surface mount adapter for model CST, 16-1/2"W x 12-1/4"H x 4-3/8"D, white or almond					5.6
69100	CTS4A						
68075	CTAMW	adapter plate for model CST, 18-1/2"W x 22"H, white or almond					2.8
68070	CTAMA						

PERFECTOE

Space saving design ideal for under cabinets

- Neatly fits under cabinets in the toe-kick area
- Perfect for kitchens, bathrooms and stairwells

grill: 18"W x 3-1/2"H x 1/2"D

rough-in: 14-1/2"W x 3-1/2"H x 8-1/4"D

*Add suffix B or W to model to designate color

Complete units require a thermostat



black part	white part	*model	description	watts	volts	amps	btus	wt/lbs
10032	10034	UC101	complete unit with wall can and grill	1000	120	8.3	3415	8.3
10027	10030	UC072	"	750/563	240/208	3.1/2.7	2560/1920	8.3
10036	10039	UC102	"	1000/750	240/208	4.2/3.6	3415/2560	8.3
66075	66076	UCT1	built-in thermostat kit for model UC, single pole, 40°F to 85°F		120/208/240	22		.3
66077	66078	UCT2	built-in thermostat kit for model UC, double pole, 40°F to 85°F		120/208/240	22		.3

SL

Efficient and uniform warmth

- Warm up in peace and quiet
- Dual exhausts help distribute heat evenly throughout the room

grill: 16-3/4"W x 12-7/8"H x 1"D

rough-in: 14-1/2"W x 10-1/8"H x 4"D

Thermostat temperature range 40°F to 85°F

For new installation, a wall can is required



part	model	description	watts	volts	amps	btus	wt/lbs
79233	SL101TW	heater assembly with thermostat and grill	1000	120	8.3	3415	8.8
79219	SL151TW	"	1500	120	12.5	5120	8.8
79218	SL151W	heater assembly and grill, no thermostat	1500/1125	120	12.5	5120	8.8
79220	SL152TW	heater assembly with thermostat and grill	1500/1125	240/208	6.3/5.4	5120/3840	8.8
79221	SL192TW	"	1900/1425	240/208	7.9/6.9	6485/4865	8.8
79230	SL252TW	"	2500/1875	240/208	10.4/9.0	8530/6400	8.8
79222	SL302TW	"	3000/2250	240/208	12.5/10.8	10240/7680	8.8
79239	SLC	wall can for model SL, single pack					4.4
79240	SLC-S	wall can for model SL, surface mount, 17"W x 13"H x 4"D, white					6.4

NLW

Quiet warmth for large rooms and entryways

- Unique fan design reduces air turbulence and noise
- Circulate air during the warmer months with the fan-only mode

grill: 16-3/4"W x 21"H x 1"D

rough-in: 14-1/4"W x 19-1/4"H x 4"D

Thermostat temperature range 40°F to 85°F

For new installation, a wall can is required



part	model	description	watts	volts	amps	btus	wt/lbs
79208	NLW208TW	heater assembly with thermostat and grill	2000	208	9.6	6825	16
79209	NLW308TW	"	3000	208	14.4	10240	16
79210	NLW408TW	"	4000	208	19.2	13650	16
79200	NLW202TW	"	2000/1500	240/208	8.3/7.2	6825/5120	16
79201	NLW302TW	"	3000/2250	240/208	12.5/10.8	10240/7680	16
79202	NLW402TW	"	4000/3000	240/208	16.7/14.4	13650/10240	16
79203	NLW452TW	"	4500/3375	240/208	18.8/16.2	15355/11515	16
79214	NLWC	wall can for model NLW, single pack					6.1
79215	NLWC-S	wall can for model NLW, surface mount, 16-5/8"W x 20-5/8"H x 4"D, white					9.2

RBF

Classic style and warmth for your bathroom

- Operation is as easy as flipping a switch
- Stainless steel grill

grill: 12"W x 19"H x 1/4"D

rough-in: 10-1/4"W x 17"H x 4"D

For new installation, a wall can is required



part	model	description	watts	volts	amps	btus	wt/lbs
79241	RBF101	heater assembly with on/off switch and grill	1000	120	8.3	3415	8
79243	RBFC	wall can for model RBF, single pack					3.9

The Hot One

Shop-tough and garage worthy

- Six-foot cord and heavy-duty bracket
- High/Low switch provides wattage choices
- 240 volt receptacle required

dimensions: 15-3/4"W x 17-1/2"H x 8-1/4"D



part	model	description	required receptacle	watts hi/low	volts	amps hi/low	btus hi/low	wt.lbs
10288	RCP402S	corded portable garage heater, red	NEMA 6-20R	4000/2667 3000/2000	240 208	16.7/11.1 14.4/9.6	13650/9100 10235/6825	29.8
10289	RCP502S	"	NEMA 6-30R	5000/3333 3750/2500	240 208	20.8/13.9 18.0/12.0	17060/11375 12795/8530	29.8

ELECTRONIC PROGRAMMABLE WALL THERMOSTATS



TH106



TH115

part	model	description	volts	amps
08160	TH106	electronic programmable single pole	120/208/240	16.7
08175	TH115-A-240D-B	electronic programmable double pole, retail pack	240/208	15
08165	TH115-A-240D-B	electronic programmable double pole	240/208	15

ELECTRONIC NON-PROGRAMMABLE WALL THERMOSTATS



TH401



TH114

part	model	description	volts	amps
72838	TH401	electronic non-programmable single pole	120/208/240	10.4
08172	TH114-A-240D-B	electronic non-programmable double pole, retail pack	240/208	15
08162	TH114-A-240D-B	electronic non-programmable double pole	240/208	15
08152	TH114-A-120-S	electronic non-programmable single pole	120	16.7

MECHANICAL WALL THERMOSTATS



T521/
T522



T410
White



T410
Almond



T410
Taupe



white part	almond part	taupe part	model	description	volts	amps
08121			T410A	non-programmable single pole, 40°F to 80°F, retail pack	120/208/240	22
08122			T410B	non-programmable double pole, 40°F to 80°F, retail pack	120/208/240	22
72801	72830	72821	T410A	non-programmable single pole, 40°F to 80°F	120/208/240	22
72802	72831	72822	T410B	non-programmable double pole, 40°F to 80°F	120/208/240	22
72865			T521-W	non-programmable single pole, 41°F to 95°F	120/208/240	22
72866			T522-W	non-programmable double pole, 41°F to 95°F	120/208/240	22

ELECTRIC BASEBOARD ACCESSORIES

*Add suffix W or A to model to designate color



SBFT2



BTF2



LTF240



BRF12



BLF

white part	almond part	*model	description	volts	amps
03400	n/a	SBFT2	Smart-Base built-in thermostat kit, electronic programmable, double pole, 40°F to 85°F, retail pack	240/208	12.6
08734	03365	BTF2	built-in thermostat kit, double pole, retail pack, 40°F to 85°F	120/208/240	22
14925	14920	BTF2	built-in thermostat kit, double pole, 40°F to 85°F	120/208/240	22
08732	03366	BTF1	built-in thermostat kit, single pole, retail pack, 40°F to 85°F	120/208/240	22
14915	14910	BTF1	built-in thermostat kit, single pole, 40°F to 85°F	120/208/240	22
14963	14960	LTF240	built-in load transfer switch receptacle kit	240	
14902	14900	BRF12	built-in receptacle requires separate supply wire	120	
14932	14930	BTF1TP	built-in thermostat kit, single pole, tamper proof, 40°F to 85°F	120/208/240	22
14942	14940	BTF2TP	built-in thermostat kit, double pole, tamper proof, 40°F to 85°F	120/208/240	22
14971	14970	BLF1	built-in corner connector, inside 90°		

softHEAT

Gentle, fluid heat for the people you love most

- Smart design helps reduce indoor allergen effects
- Hydronic heat installs easily with no plumbing required

dimensions: 9-1/2"H x 3-1/4"D x various lengths

* Add suffix W or WS to model to designate color
All models require a thermostat



NEW

NEW

white part	white sand part	*model	description	watts	volts	amps	btus	wt/lbs
13111	13116	EBHN500-1	35" hydronic baseboard, left hand wire	500	120	4.2	1710	17
13112	13117	EBHN750-1	47" hydronic baseboard, left hand wire	750	120	6.3	2560	21.2
13113	13118	EBHN1000-1	59" hydronic baseboard, left hand wire	1000	120	8.3	3415	26.1
13114	13119	EBHN1250-1	71" hydronic baseboard, left hand wire	1250	120	10.4	4265	31.4
13115	13120	EBHN1500-1	83" hydronic baseboard, left hand wire	1500	120	12.5	5120	35.6
13162	13151	EBHN500-8	35" hydronic baseboard, left hand wire	500	208	2.4	1710	17
13163	13152	EBHN750-8	47" hydronic baseboard, left hand wire	750	208	3.6	2560	21.2
13164	13153	EBHN1000-8	59" hydronic baseboard, left hand wire	1000	208	4.8	3415	26.1
13165	13156	EBHN1250-8	71" hydronic baseboard, left hand wire	1250	208	6.0	4265	31.4
13166	13154	EBHN1500-8	83" hydronic baseboard, left hand wire	1500	208	7.2	5120	35.6
13157	13100	EBHN500	35" hydronic baseboard, left hand wire	500/375	240/208	2.1/1.8	1710/1280	17
13158	13101	EBHN750	47" hydronic baseboard, left hand wire	750/563	240/208	3.1/2.7	2560/1925	21.2
13159	13102	EBHN1000	59" hydronic baseboard, left hand wire	1000/750	240/208	4.2/3.6	3415/2560	26.1
13160	13103	EBHN1250	71" hydronic baseboard, left hand wire	1250/937	240/208	5.2/4.5	4265/3200	31.4
13161	13104	EBHN1500	83" hydronic baseboard, left hand wire	1500/1125	240/208	6.3/5.4	5120/3840	35.6
13211	13216	EBHN500-1	35" hydronic baseboard, right hand wire	500	120	4.2	1710	17
13212	13217	EBHN750-1	47" hydronic baseboard, right hand wire	750	120	6.3	2560	21.2
13213	13218	EBHN1000-1	59" hydronic baseboard, right hand wire	1000	120	8.3	3415	26.1
13214	13219	EBHN1250-1	71" hydronic baseboard, right hand wire	1250	120	10.4	4265	31.4
13215	13220	EBHN1500-1	83" hydronic baseboard, right hand wire	1500	120	12.5	5120	35.6
13262	13251	EBHN500-8	35" hydronic baseboard, right hand wire	500	208	2.4	1710	17
13263	13252	EBHN750-8	47" hydronic baseboard, right hand wire	750	208	3.6	2560	21.2
13264	13253	EBHN1000-8	59" hydronic baseboard, right hand wire	1000	208	4.8	3415	26.1
13265	13256	EBHN1250-8	71" hydronic baseboard, right hand wire	1250	208	6.0	4265	31.4
13266	13254	EBHN1500-8	83" hydronic baseboard, right hand wire	1500	208	7.2	5120	35.6
13257	13200	EBHN500	35" hydronic baseboard, right hand wire	500/375	240/208	2.1/1.8	1710/1280	17
13258	13201	EBHN750	47" hydronic baseboard, right hand wire	750/563	240/208	3.1/2.7	2560/1925	21.2
13259	13202	EBHN1000	59" hydronic baseboard, right hand wire	1000/750	240/208	4.2/3.6	3415/2560	26.1
13260	13203	EBHN1250	71" hydronic baseboard, right hand wire	1250/937	240/208	5.2/4.5	4265/3200	31.4
13261	13204	EBHN1500	83" hydronic baseboard, right hand wire	1500/1125	240/208	6.3/5.4	5120/3840	35.6
13170	13132	EBKN	built-in thermostat kit, double pole, 40°F to 85°F		240/208	25		1

ELECTRIC BASEBOARD

Sensible, quiet heat starts here

- Simple installation with pre-punched knockouts
- Proven construction maximizes surface area and funnels heated air

dimensions: 6-3/4"H x 2-1/2"D x various lengths

* Add suffix W or A to model to designate color
All models require a thermostat

Accessories on page 5



white part	almond part	*model	description	watts	volts	amps	btus	wt/lbs
05530	05520	2F500-1	30" baseboard	500	120	4.2	1710	6.3
05532	05522	3F750-1	36" baseboard	750	120	6.3	2560	7.3
05534	05524	4F1000-1	48" baseboard	1000	120	8.3	3415	9.4
05536	05526	6F1500-1	72" baseboard	1500	120	12.5	5120	13.6
11924	11918	2F500-8	30" baseboard	500	208	2.4	1710	6.3
11934	11938	3F750-8	36" baseboard	750	208	3.6	2560	7.3
11944	11948	4F1000-8	48" baseboard	1000	208	4.8	3415	9.4
11954	11958	5F1250-8	60" baseboard	1250	208	6.0	4265	11.9
11964	11968	6F1500-8	72" baseboard	1500	208	7.2	5120	13.6
11984	11988	8F2000-8	96" baseboard	2000	208	9.6	6825	17.9
10924	11990	8F2500-8	96" baseboard	2500	208	12.0	8530	17.9
09949	06501	2F350	24" baseboard	350/262	240/208	1.5/1.3	1195/895	5.9
09950	06502	2F500	30" baseboard	500/375	240/208	2.1/1.8	1710/1280	6.3
09952	06508	3F750	36" baseboard	750/563	240/208	3.1/2.7	2560/1925	7.3
09954	06509	4F1000	48" baseboard	1000/750	240/208	4.2/3.6	3415/2560	9.4
09955	06510	5F1250	60" baseboard	1250/937	240/208	5.2/4.5	4265/3200	11.9
09956	06511	6F1500	72" baseboard	1500/1125	240/208	6.3/5.4	5120/3840	13.6
09958	06513	8F2000	96" baseboard	2000/1500	240/208	8.3/7.2	6825/5120	17.9
09960	06515	8F2025	96" baseboard	2500/2000 1875/1500	240 208	10.4/8.3 9.0/7.2	8530/6825 6400/5120	17.9
03360	03358	8F2500	96" baseboard	2500/1875	240/208	10.4/9.0	8530/6400	17.9

Made for your family, built by ours

The comfort of your home begins at our home in the Pacific Northwest. Every Cadet heater is designed, developed and manufactured at our facilities in Vancouver, Washington, USA. It's been that way since we started making heaters back in 1957. We're a family-run business, so it's simple: we build the heaters that we'd want to keep our families comfortable and safe.

The finest heaters. The best price. Built here in the USA.



Some things are worth doing right

CADET 
INVITING WARMTH
toll free 855.CADET.US
(855.223.3887)
cadetheat.com